




### Key Features

- 2/3/4/5Mega Pixel Available
- Full 1080p real time video
- Infra Red Illumination (90m available)
- IP66
- Internal POE available

### Dimensions



Units in mm

### RT – LNB - 2 / 3 / 4 / 5

Camera	
Image Sensor	2MP OV9732, 3MP IMX323, 4MP OV4689, 5MP IMX178
Effective Pixels	2MP 1280*720 / 3MP 1985*1105 / 4MP 2065*1553 / 5MP 2592*1944
Sound to Noise Ratio	>52db
Main Processor	Hi3518EV200 / Hi3516CV200 / Hi3516D / Hi3516A
Compression	H.264 / JPEG / AVI / MJPEG
TV System	PAL/NTSC
Electronic Shutter time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Scanning System	Progressive
Video Output	Network
Pixels	2MP / 3MP / 4MP / 5MP
Lens Type	Manual
Motion Detection	Supported
Privacy Masking	3 Rectangular Zones
LENS	
Focus Length	2.8 -12mm (6MP – 3.6mm)
Focus Control	Manual (auto available)
NIGHT VISION	
Infrared LED	42 x 4 PCS
IR Range	60 Metres (90m available)
Auto Control IR LED	Under 10 lux
NETWORK	
Network Protocol	TCP/IP, DHCP, SMTP, DDNS, DNS, PPPoE, P2P
ONVIF	Supported
Network Interface	Built in RJ 45 network interface supports 10/100m IP DATA
GENERAL	
Weatherproof	IP66
Operating Temperature	-20 ~ +60
Storage Temperature	-20 ~ +60
Heater & Blower	N/A
Power	DC 12V+-10% 1000mA
IR cut Filter	Yes
Dimensions	220 W x 80 H x 80 D mm
Weight	1400 g

### Accessories



Advanced Keyboard – AKBD

9 Channel NVR – NVR9